



Tehnički podaci :

Napajanje	100 - 240V~ 50/60Hz
Snaga	350W max / 100W at 1/8 output power
Frekvencijski raspon	80 – 20000Hz +/-1dB
Omjer signala i šuma	SNR~95dB, A-weighted
Distorzija	<0.1% according to IEC 60268
Pojačanje po kanalu	-100dB +10dB, 1dB steps
Digitalna Obrada Signala	Integrated - 48 kHz, 24 bits - 344 MIPS
BGM audio inputs	1 x balanced audio 1 Vrms. 10 K Ω , 3 Pin, Euroblock type
Prioritetni audio ulazi	2 x balanced audio 1 Vrms. 10 K Ω , 4 Pin, Euroblock type (GPIO)
Glavna kontrola (GPIO)	2 x control I/O, 0-5 V, 100 Ω , in PRIO audio inputs
LDA ACSI Bus	1 x balanced audio 1 Vrms. 10 K Ω , RJ-45 female, total 800m / 2624.7ft
Mogućnost spajanja ACSI-Link	2 x balanced audio 1 Vrms. 10 K Ω , RJ-45 female, total 800m / 2624.7ft
Pretpojačala	4 x balanced audio 1 Vrms. 100 Ω , 3 Pin, Euroblock type
Atenuatori	6 x override 24V DC, 6 x 30mA, 2 Pin, Euroblock type (4 pin connector)
Emergency kontrolni ulazi	8 x 0 - 5V DC, monitored inputs, 2 Pin, Euroblock type (4 pin connector)
Emergency kontrolni izlazi	2 x contact closure output, NO, max 60V DC 130mA, 2 Pin, Euroblock type (4 pin connector)
Virtualna matrica	15 x 24 maximum
Pojačala	2 x 500W D class (250Wrms x 2) @ 70 / 100V. Min load 20 Ω
Rezervna pojačala	1 backup amplifier with automatic priority according to EN 54-16
Izlazni zvučničkih linija	6 x 100V audio. Min. impedance: 20 Ω 500W (outputs 1 and 2), 80 Ω 120W (rest), 2 Pin, Euroblock type
Izlazna snaga	500 W according to EN60065. 200 Wrms according to EN 54-16
Zaštita	Over-temperature, infrasonic, short circuit, slow start-up, overload
Rezervno napajanje	181x76x167mm battery housing, up to 22Ah
Punjač baterije	Integrated, smart charging up to 3 amperes
Ekran	Backlit LCD 2 rows x 16 characters
Uvjeti radne okoline	-5 $^{\circ}$ C to +45 $^{\circ}$ C / 23 $^{\circ}$ F to 113 $^{\circ}$ F 5% to 95% relative humidity (without condensation)
Izvedba kućišta	Materials: Fe y AL Colours: RAL7016 and RAL9005
Težina	7.5 Kg / 15.76 lb
Dimenzije (W x H x D)	453mm x 88mm x 455mm / 18.2" x 3.46" x 18"
Dodaci	Male Euroblock connectors, installation screws, 4 x rubber foot

