



Kompaktna telefonska centrala sa dva sučelja za analogne telefone, integriranim GSM gateway i VoIP mogućnostima.

Analogna sučelja AB (FXS)	2
IP kanali	2
IP trunks (SIP)	8
IP pretplatnici (SIP)	8
GSM trunks (2G)	1
CTS IP sistemska sučelja	8
SN / RL sučelja	1/1
Imenik	1000
Ethernet 10/100 sučelja	1
Podržani uređaji	Slican IP telefoni, VoIP telefoni (SIP), analogni telefoni, Slican DPH parlafoni, Slican konzole, Slican HLP-22, MSB-1102 i MAB-1101
Aplikacije koje podržavaju IPS-08	Slican CTI Communicator (MessengerCTI i WebCTI), Slican BillingMAN/BillingMAN.plus, Slican ConfigMAN.admin/ConfigMAN.user
VoIP parametri	SIP 2.0, kodeci G.711a, G.711 $\mu$ . Mod rada: VoIP master ili slave
Protokoli	POTS / SIP 2.0 / 1800 / 1900; CTIP / HOTELP / TAPI / HTTP / XML
Napajanje	~230 V, 50 Hz, <15 VA (vanjsko 12 V, 1,2 A)
Dimenzije (V-Š-D)	191 x 111 x 36 mm
Težina	300 g